This listing of claims will replace the prior version in the application.

## **Claims**

- 1. (currently amended) Composition according to Claim 1, comprising from 1 to 40% by weight of fluorinated base, from 50 to 99% by weight of secondary butanol, and from 0 to 30% by weight of DMSO, the sum of the percentages by weight of the constituants being equal to 100.
- 2. (original) Composition according to Claim 1, comprising from 15 to 25% by weight of fluorinated base, from 50 to 70% by weight of secondary butanol and from 15 to 25% by weight of DMSO.
- 3. (currently amended) Composition according to one of Claims 1 or 2 Claim 1, characterized in that the fluorinated base comprises one or more fluorinated compounds having a surface tension of less than 30 mN/m at 25°C and a zero ozone degradation potential (ODP).
- 4. (currently amended) Composition according to Claim 3, characterized in that the fluorinated eompound(s) is (are) compound is chosen from the group consisting of hydrofluorocarbons (HFCs) and/or, hydrofluoro ethers (HFEs) and mixtures thereof.
- 5. (currently amended) Composition according to one of Claims 1 to 3

  <u>Claim 1</u>, characterized in that the fluorinated base also contains trans-1,2-dichloroethylene.
- 6. (currently amended) Composition according to Claim 4, characterized in that the HFC(s) is (are) HFC is chosen from 1,1,1,3,3-pentafluorobutane (HFC 365 mfc), 1,1,1,2,3,4,4,5,5,5-decafluoropentane (HFC 4310 mee), 1,1,1,2-tetrafluoroethane (HFC 134 a), pentafluoroethane (HFC 125), 1,1,1-trifluoroethane (HFC 143 a), difluoromethane (HFC 143 a), di

- 32), 1,1-difluoroethane (HFC 152 a), 1-fluoroethane (HFC 161), 1,1,1,2,3,3,3heptafluoropropane (HFC 227 ea), 1,1,1,3,3,pentafluoropropane (HFC 245 octafluoropropane (HFC 218), (perfluorobutyl)ethylene (C<sub>4</sub>H<sub>9</sub>CH=CH<sub>2</sub>), 1,1,2,2,3,4,5heptafluorocyclopentane  $(C_5H_3F_7)$ , perfluorohexylethylene  $(C_6F_{13}CHCH_2)$ , tridecafluorohexane (C<sub>6</sub>F<sub>13</sub>H) and , perfluoro(methylmorpholine) (PF 5052) or mixtures thereof.
- 7. (currently amended) Composition according to one of Claims 4 to 6

  Claim 4, characterized in that the fluorinated base comprises a mixture of HFC 365 mfc and HFC 4310 mee and, optionally, HFC 227 ea.
- 8. (currently amended) Composition according to Claim 4, characterized in that the HFE(s) is (are) HFE is chosen from methylheptafluoropropyl ether ( $C_3F_7OCH_3$ ), methylnonafluorobutyl ether ( $C_4F_9OCH_3$ ), ethylnonafluorobutyl ether ( $C_4F_9OC_2H_5$ ) and perfluoropyran ( $C_5F_{10}O$ ) or mixtures thereof.
- 9. (currently amended) Use of the compositions according to one of Claims 1 to 8, Method for defluxing electronic boards ,more particularly for defluxing electronic boards containing "no clean" fluxes comprising a cleaning step, characterized in that the cleaning step is carried out with a composition according to Claim 1.
- 10. (currently amended) Method for defluxing electronic boards of Claim 9 comprising a first cleaning step and a second rinsing step, characterized in that the cleaning step is carried out with a composition according to one of Claims 1 to 8 Claim 1, in a cleaning tank (2) and the rinsing step is carried out with a pure fluorinated base in a rinsing tank (8), this fluorinated base possibly being different from that present in the cleaning tank (2).

Respectfully submitted,

Steven D. Boyd

Steven D. Boyd Attorney for the Applicants Reg. No. 31,000

Arkema, Inc. 2000 Market Street Philadelphia, PA 19103-3222 Tel (215) 419-5270 Fax (215) 419-7075 Date: February 22, 2006